

IS-5041 Self-Install Guide

Replacement STB Installation

To ensure the successful installation of your IS-5041 Set Top Box, please read and follow the step-by-step instructions below.

Do you have all the necessary equipment?

- IS-5041 Set Top Box
- Remote Control (this RC is already programmed to operate your STB. Instructions on how to program your remote to operate your TV or other devices are available upon request.)
- HDMI Cord
- Power Cord



Power Cord

HDMI Cable



- 1.** Make sure your TV is turned off.
- 2.** Connect the HDMI Cable from the HDMI port on the back of the STB to the HDMI input on your TV.
- 3.** Turn on your TV. Make sure that your TV is set to the proper input.
- 4.** Plug one end of the STB power cord into the STB, and the other end into the power outlet.
- 5.** As the STB starts up, it will display the following message: **No network connection. Make sure the network cable is connected or press OK to setup WIFI.**
- 6.** At this point you are now going to connect your new STB to your WIFI access point (aka router). Press OK on the remote control to start the association process on the new STB. You will now see the WIFI Setup menu on the TV showing the available WIFI networks. Select the correct WIFI network.
- 7.** Enter your WIFI password. The STB will connect to the network and finish STB setup automatically.
- 8.** In a few seconds, the new set top box should indicate that it has connected with the following message: WIFI connected. Waiting for network setup.
- 9.** As your STB loads, you will see a welcome screen indicating the STB is loading with the following message: **Hello, we're getting things ready for you.**
- 10.** Once the STB has loaded you are ready to stream. Enjoy your Norvado TV!

